

# **Coldrink 2 MC System**

Delivers premium quality water for fountain applications.

## **DESCRIPTION:**

- Reduces chlorine taste and odor and other offensive contaminants
- New and improved Micro-Pure II media inhibits the growth of bacteria
- Improves the taste of fountain beverages and helps retain the drink's carbonation
- Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces health contaminants such as cysts
- Protects drink system seals, pump, tubing and small orifices from clogging, corrosion and abrasive wear
- 20" prefilter reduces dirt and particles
- Manifold features water shut off, flushing valve, inlet and outlet pressure gauges
- Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination
- NSF Certified under NSF/ANSI Standards 42 and 53

## **Features:**

- Asbestos Reduction
- Bacteriostatic\*
- Chlorine Reduction
- Cyst Reduction
- Micropure II
- Particulate Reduction
- Taste & Odor

**Capacity:** 18,000 gallons (68, 400 L)

**Maximum Flow:** Maximum 3.34 gpm (12.6 Lpm)

**Can Size:** 7

**Qty. per Case:** 1

**Micron Rating:** 0.50

**Working Pressure:** 10 - 125 psi (0.7 – 8.6 bar), non-shock

**Max. Temp:** 35 - 100°F (2 - 38°C)

**Inlet Outlet Size:** 3/4"

**Operating Weight:** 29 lbs

**Shipping Weight:** 20 lbs

**H:** 25.59" **W:** 21.5" **D:** 6" **Certifications:** NSF42 NSF53