

<b>KARAKTERİSTİK ÖZELLİKLER / CHARACTERISTICS</b>		
Climate class		4
Temperature range	(°C)	+1 / +10
Energy consump.	(kWh/24h)	4.60
Power	( W )	230
Voltage/freq.	( V / Hz.)	230 V / 50 Hz.
Current Consumption	A	1.7
Relative running time	( % )	60
<b>AKSESUARLAR VE KONTROL LAMBALARI / ACCESSORIES AND CONTROL LAMPS</b>		
Adjustable thermostat		+
Mains supply lamp		-
Female Elect. Plug		H05 V V - F 3x1 mm with EU plug
Internal light		TLD15W, fluorescent L= 438mm
Door Lock		+
Shelf		2
Adjustable height		+ 4 köşede/on 4 corners
Wheel		-
<b>TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATIONS</b>		
External dims.	(WxDxH)	650 x405x940mm
Internal dims.	(WxDxH)	590x260x632 mm
Pack. dims.	(WxDxH)	740x460x1050 mm
Gross volume	(lt)	100
Net volume	(lt)	90
Gross weight	(kg)	51
Net weight	(kg)	45.5
Outer body		0,5 mm.DKP / sheet steel
Outer body paint		60~70µ toz boya / powder paint
Inner liner		ANTIŞOK/THERMOFORM
Insulation material		Sert P.U. / Rigid P.U.
Insulation density		36kg/m <sup>3</sup>
Compressor		ACC 45 TB
Overload protector		T0068
Relay		MTRP 26
Capacitor		47-56/250
Comp. ventilator		GAMAK 36,5W 250V/50Hz
Evaporator		ROLLBOND
Evap. ventilator		KARE FAN 230V/50Hz.120mA 19W
Condenser		FIN TIPI KONDENSER
Thermostat		K50-L 3421
Dryer-filter		7,5 Gr.
Refrigerant		R134a
Refrigerant charge	(gr )	110 Gr.